

Canon**XF705**

RESOLUTIE	KLEURSAMPLING	BITDIEPTE	FRAMERATE	CODEC	Mbps
3840 x 2160	YCC 4:2:2	10-bit	59.94P, 29.97P, 23.98P, 50.00P, 25.00P	H.265/HEVC	160Mbps/110Mbps
1920 x 1080	YCC 4:2:2	10-bit	59.94P, 29.97P, 23.98P, 50.00P, 25.00P	H.265/HEVC	60Mbps/45Mbps
			59.94i, 50.00i		60Mbps/45Mbps
			120P, 100P		180Mbps
3840 x 2160	YCC 4:2:0	8-bits	29,97P, 23,98P, 25,00P	H.264/XF-AVC	160Mbps
1920 x 1080	YCC 4:2:0	8-bits	59.94P, 29.97P, 23.98P, 50.00P, 25.00P	H.264/XF-AVC	45Mbps
			59.94i, 50.00i	H.264/XF-AVC	35 Mbps
			120P, 100P	H.264/XF-AVC	45Mbps
1280 x 720	YCC 4:2:0	8-bits	59,94P	H.264/XF-AVC	180Mbps
1280 x 720	YCC 4:2:0	8-bits	59,94P	H.264/XF-AVC	8Mbps
1920 x 1080	YCC 4:2:0	8-bits	59.94P, 29.97P, 23.98P, 50.00P, 25.00P	H.264/MP4	35Mbps/8Mbps